

Stinger THT 5 Channel Charger

aspilsan
Energy of Technology



5 Channel Charger for 34 Series Stinger THT Batteries (Ni-MH)

Charger Specification

Rechargeable Battery Type	34 series Ni-MH(Nickel-metal hydride)	Case Material	Plastic
Charger Input Voltage	100-240VAC Rated frequency: 50/60Hz	Width	370mm±20mm
Charger Output Voltage	Max. Voltage (At no load): 66-70Vdc Rated Voltage: 27.2-51V	Length	580mm±20mm
Maximum Output Current	500mA	Height	250mm±20mm
Trickle Current	20-30mA (Pulse ratio 1/20 ± 5mA)	Weight	10000gr±50gr.
-ΔV Detect	-5mV	Storage Temperature Range	-40°C - 70°C
Charging Method	Pulse Charging - ΔV Detection - Trickle Current		
Protection	Short Circuit, Reverse Polarity, Over Temperature (Battery Package Temperature <65 °C)		
Charge Indicator	Red: In Charging Mode Green: Fully Charged/No Load Red LED Blinking: in Short Circuit or polarity reverse Green LED Blinking: repair the charging with smal current		
Operating Temperature Range	Charge	-20 - 45°C	



ASPİLSAN Enerji A.Ş.

Türk Silahlı Kuvvetlerini Güçlendirme Vakfı'nın Bir Kuruluşudur.

ASPİLSAN Enerji A.Ş.
Pil ve Batarya Sistemleri Üretim Tesisi
Mimarsinan OSB Mahallesi
1. Cadde No:43 Melikgazi / Kayseri
Tel: +90352 321 12 15-16
Faks: +90352 321 12 17

aspilsan.com